



SOUTHWIND

FLOORS FOR LIFE

PRODUCT SPECIFICATION

Style Number	W090D
Style Name	Classic Strip
Construction	Class III High Performance LVP
Wear Layer Finish	Urethane with Double UV Coating
Wear Layer Thickness	20 mil
Overall Thickness	6.5mm (4 mm WPC/1mm IXPE/1.5mm Vinyl top)
Attached Cushion	1mm IXPE Cross Linked Polyethelene

FEATURES

Plank Edge	Micro Bevel
Texture	EIR (Embossed in Register)
Plank Size	3.26" Width / Mixed Lengths 19.69"/39.37"/60"
Installation	Floating

TESTING

Impact Sound Conduction / ASTM E492-09	IIC 61
Sound Transmission Class /ASTM E90-09	STC 52
Slip Resistance / ASTM D2047	0.86 Dry / 0.90 Wet
Dimensional Stability / ASTM F2199	Pass
Residual Indentation / ASTM F1914	Pass
Static Load Limit / ASTM F970	Pass
Resistance to Heat / ASTM F1514	Pass
Resistance to Light / ASTM F1515	Pass
Resistance to Chemicals / ASTM F925	Pass
Radiant Flux / ASTM E648	>0.45 watts/cm², NFPA Class I
Smoke Density / ASTM E662	Pass, <450

WARRANTY

Lifetime Residential
10 Year Commercial

ENVIRONMENTAL

Indoor Air Quality	GREENGUARD Gold certified FloorScore® certified
--------------------	--