



RockLock Plus

☞ SPECIFICATIONS

Plank Size:	7.09" x 48.03"
Overall Thickness:	6 mm
Product Construction:	5 mm Rigidcore + 1.0 mm MaxStepPro™
Wear Layer:	20 mil with MaxProtect®
Edge:	ColorEdge®
Embossing:	GenuWood™
Installation Method:	Angle-Tap
Recycled Content:	None
Certifications:	GREENGUARD Gold®

Classification	(ASTM 3261-17)	Class III, Type B
Chemical Resistance	(ASTM F 925)	Passes
Critical Radiant Flux	(ASTM E 648-06)	Passes
Dimensional Stability	(ASTM F 2199)	Passes
Residual Indentation	(ASTM F 1914)	Passes
Resistance to Heat	(ASTM F 1514)	Passes
Resistance to Light	(ASTM F 1515)	Passes
Smoke Density	(ASTM E 662)	Passes
Thickness	(ASTM F 387)	Passes
Static Load Limit	(ASTM F 970)	Passes
Impact Insulation	(ASTM E492-09)	IIC 60
Sound Transmission	(ASTM E90-2009)	STC 62

☞ PACKAGING

Square Feet Per Carton:	18.91	Pieces Per Carton:	8
Square Feet Per Pallet:	1,229.15	Cartons Per Pallet:	65
Square Feet Per Container:	24,583.25	Pallets Per Container:	20
Weight Per Carton:	40.35 lbs	Weight Per Pallet:	2,622.75 lbs

☞ COLOR LINE

60181 Afton	60037 Cass	60087 Hinkleville	60041 Lewisburg	60061 Tunnelton
60182 Albright	60072 Davis	60088 Imperial	60062 Rowlesburg	60051 Wisp
60183 Aurora	60078 Dunmore	60089 Kanawha	60042 Snowshoe	
60036 Bartow	60086 Goshen	60077 Ketterman	60071 Thomas	

☞ WARRANTIES

Lifetime Limited Waterproof*	Lifetime Limited Residential*	10 Year Limited Light Commercial*
------------------------------	-------------------------------	-----------------------------------

*Please visit our website for full warranty details.